PEGASUS BP-4001



Next Generation Barcode Printer



With superior performance and affordable price, these 203dpi(8 dots/mm), Direct Thermal/Thermal transfer printers are best in their class. The Pegasus BP Series models are delivered stock out of the box with competitive emulations onboard, optimal interfaces (built in USB standard)

Pegasus BP-4001 printer is a cost-effective desktop printer, Graphical User Interface in LCD display makes menu friendly to users; Four LED buttons let operation is easy; Multiple communication ports can fit for different interfaces; USB keyboard or scanner works with LCD for standalone operation; SD slot enlarge the data storage; Real time clock is built-in for time and date printing application; Buzzer sound warns the users at noisy working place; Adjustable see-through and reflective sensor detects labels without mistakes.







ww.pegasustech.net mkt@pegasustech.ne

Featuring

- ▶ EPL Language Support
- Multilingual LCD display
- ▶ 4 LED buttons indication
- Convenient form operation
- Multiple communication ports,
- ▶ 4MB Flash memory, 8MB SDRAM
- Keyboard or scanner with USB interface for standalone operation
- Buzzer with red flash light for noisy working place





Ideal for these applications:

Healthcare

- Document archiving
- Specimen labeling
- Sterile services labeling
- thermal transfer
- patient identification

Manufacturing

- agency labels
- product labeling

Retail

- outdoor product labeling
- retail pharmacy labeling and safety labels
- Speciality printing

Security

- asset marking
- evidence tracking

Supply Chain

- product and shipping
- bels for outdoor use




www.pegasustech.net mkt@pegasustech.ne

Pegasus BarDesigner Feature

- A full range of tools
- Freeware Software
- Multilingual Interface
- Database support
- Professional Edition Features
- Support labels and forms making







Specification

CPU AND MEMORY

- CPU: 32-bit CPU
- MEMORY: 8MB SDRAM, 4MB Flash ROM, SD slot (up to 4GB)

PRINT

- RESOLUTION: 203 dpi/300 dpi
- PRINT MODE :
- PRINT SPEED: 1" to 4" ips
- MAX. PRINT LENGTH: 150 inches
- PRING WIDTH: 4.1" (104mm)
- BARCODE :

1D: Code39, Code93, Code128 UCC, Code128 auto, Codabar, EAN8, EAN13, Interleaved 2 of 5, UCC/EAN 128, UPC A, UPC E, UPC Interleaved 2 of 5, EAN-14, German Post Code, Industrial 2-of-5, Japanese Postnet, Logmars, MSI, MSI-3, Plessey, Postnet, RSS

2D: Data Matrix, MaxiCode, PDF417, QR code, Aztec, Codablock, Code 49

FONT: 5 internal expandable bitmap fonts
 (alpha-numeric) 2 internal expandable bitmap fonts (numeric only)

Downloadable soft font 4 directions : 0, 90, 180, 270 degrees

• IMAGE : PCX, Direct binary graphic

SENSOR TYPE

Moveable reflective and see-through sensor, Label sensor, Cover open sensor, ribbon sensor

DISPLAY

Backlight LCD display 128x64 dots

CONTROL PANEL

4 multi-functional keys, 4 status LED light, 1 error LED light

MEDIA

- WIDTH: 0.59"~4.33"(15mm~110mm)
- MEDIA ROLL DIAMETER: ID-1" (25.4mm)/OD-Max. 5"(127mm)
- MEDIA THICKNESS: 0.002" (0.06mm) to 0.0075" (0.2mm)
- MEDIA TYPE: Continuous, die-cut, tag, fan-fold, black mark

RIBBON

- WIDTH: 1.0" (25.4mm) to 4.3" (110mm)
- RIBBON ROLL DIAMETER : ID 0.5"/OD 1.535"
- RIBBON LENGTH: Max. length 100M
- RIBBON TYPE : Wax, wax/resin, resin

INTERFACE

Serial, Parallel, USB master and slave, Ethernet 10/100Mbps (option)

POWER

Switching power adapter - Input: 100 to

240V/Output: 24V

AUDIO

Beep sound when error occurs

OPTION

Peeler kit, Cutter, Ethernet module

OPERATING (STORAGE) TEMPERATURE $^{\circ}$ C

PRINTER DIMENSION

200(W) x 263(L) x 188(H) mm, Weight: 2KG

CERTIFICATION

CE, FCC class B, CCC, CB

Pegasus Exclusive Supplies

Pegasus offers a wide range of supplies for your BP4001series printers, all made to a high standard and suitable for a variety of applications.

- Manufactured exclusively for Pegasus printers
- Laboratory-tested for optimum performance

For More detail visit our website: www.pegasustech.net





www.pegasustech.ne