



Pegasus Xtreme 9000 POS

The POS more than you can ever ask



Specification Sheet

Pegasus Model		Xtreme-9000		
CPU Support		Intel Bay Trail- D J1900 2G	Intel Haswell Pentium G3320TE 2.3G Core i3-4330TE 2.4G Core i5-4570TE 2.7G	Intel Apollo Lake Celeron N3350 2.4G Pentium N4200 2.5G
System Memory		DDR3L SO-DIMM x 2, 2GB (Max. 8GB)	DDR3L SO-DIMM x 2, 4GB (Max. 16GB)	DDR3L SO-DIMM x 2, 4GB (Max. 16GB)
Storage	HDD	320GB 2.5" x 1		
	SSD	SSD x 1 (Optional)		
LCD	Size	15" TFT LED LCD Panel		
	Brightness	350cd/m2 (Typ.)		
	Resolution	1024 x 768		
Touch Screen	True-Flat Projected Capacitive Touch			
Tilt Angle	0 ~ 120 degree			
External I/O Port	6 x USB 2.0 Ports		4 x USB 2.0 & 2 x USB 3.0 Ports	
	3 x Serial port (RJ45); (COM1~3: 0/5/12V by BIOS)			
Rear	1 x VGA (Power enable by BIOS; +12V)			
	1 x Cash Drawer Port (RJ11; +12V)			
	1 x LAN (10/100/1000)			
	1 x Mic-In/Speaker-out (Combo Jack)			
	1 x DC In			
	1 x Power Switch			
	2 x 2W speaker (Optional)			
Speaker	2 x 2W speaker (Optional)			
Power	External power adapter, 60W/12V (Lock type)	External power adapter, 80W/12V (Lock type)	External power adapter, 60W/12V (Lock type)	
EMC Safety	CE, FCC Class A			
Environment	Operating Temperature	0°C ~ 35°C		
	Storage Temperature	-20°C ~ 60°C		
	Operating Humidity	20% - 85% RH non condensing		
	Storage Humidity	20% - 85% RH non condensing		
OS Support	Windows® 7 Professional / Windows® Embedded POSReady 7 / Windows® Embedded 8.1 Industry / Windows® 10 IoT / Linux per request		Windows® 10 IoT / Linux per request	
Dimension (W x D x H)	340 x 284 x 320 cm			
Weight (N.W./G.W.)	6 kgs(N.W.)/7 kgs(G.W.)			
Wall Mount	VESA 100 x 100mm			
MSR (USB)	MSR / MSR + Finger Print (Combo) / MSR + iButton (Combo) / MSR + RFID (Combo)			
	Customer display (USB)	Flush mount VFD display, 2x20 characters		
	2nd Display	9.7" (1024 x 768)		